## **List of Current Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1 - 12 (Cancelled).

13. (Currently Amended) A method for measuring a fill level of a fill substance in a container and for monitoring at least one predetermined fill level ( $L_{MIN}$ ,  $L_{MAX}$ ), using a fill level measuring device working according to a travel-time principle, comprising the steps of:

sending, in each measuring cycle, transmission signals (S) toward the fill substance and receiving their echo signals (E);

deriving an echo function from the echo signals (E) which represents an amplitude of the echo signals (E) as a function of travel-time (t) for determining the exceeding or falling beneath of the predetermined fill levels ( $L_{MIN}$ ,  $L_{MAX}$ ); and

determining a measure for the area under the echo function in a region (I, II) of particular travel-time ( $t_{MIN}$ ,  $t_{MAX}$ ) to be expected for the predetermined fill level ( $L_{MIN}$ ,  $L_{MAX}$ )

determining the fill level, based on the echo signals (E), according to a first evaluation, and based on the echo signals (E), according to a second evaluation independent of the first evaluation; and

observing whether the fill level exceeds or falls beneath the predetermined fill level ( $L_{MIN}$ ,  $L_{MAX}$ )[[.]], wherein:

it is detected that the fill level exceeds the particular predetermined fill level ( $L_{MIN}$ ) when the measure exceeds a predetermined reference measure;

it is detected that the fill level falls beneath the particular predetermined fill level (L<sub>MIN</sub>, L<sub>MAX</sub>) when the measure falls beneath a predetermined reference measure, and said measure corresponds to an integral over the echo function in the region (I, II) of the particular travel-time (t<sub>MIN</sub>, t<sub>MAX</sub>) to be expected for the predetermined fill level (L<sub>MIN</sub>, L<sub>MAX</sub>).

## Claim 14 (Cancelled)

- 15. (Previously presented) The method as claimed in claim 13, wherein: the echo signals (E) applied for determining the fill level are conditioned by a first signal processing branch of the fill level measuring device.
- 16. (Previously presented) The method as claimed in claim 13, wherein: the echo signals (E) applied for detecting the exceeding or falling beneath of the fixedly predetermined fill levels (L<sub>MIN</sub>, L<sub>MAX</sub>) are conditioned by a second signal processing branch of the fill level measuring device.

## Claims 17 and 18 (Cancelled)

- 19. (Currently Amended) The method as claimed in claim [[17]] 13, wherein: said measure corresponds to an average value, median or maximum of the amplitudes of the echo function in the region (I, II) of the travel-time (t<sub>MIN</sub>, t<sub>MAX</sub>) to be expected for the predetermined fill level (L<sub>MIN</sub>, L<sub>MAX</sub>).
- 20. (Previously presented) The method as claimed in claim 13, further comprising the steps of:

deriving an echo function from the echo signals (E), which represents an amplitude of the echo signals (E) as a function of a travel-time (t) for determining the exceeding or falling beneath of the predetermined fill levels ( $L_{MIN}$ ,  $L_{MAX}$ );

determining a first measure for area under the echo function in the region (I, II) of a particular travel-time ( $t_{MIN}$ ,  $t_{MAX}$ ) to be expected for a particular predetermined fill level ( $L_{MIN}$ ,  $L_{MAX}$ );

a comparison measure is, in the same way, determined for a predetermined reference region (R) of the echo function, and, based on a comparison of the particular first measure with the comparison measure, it is determined whether the fill level exceeds or falls beneath the particular predetermined fill level ( $L_{\text{MIN}}$ ,  $L_{\text{MAX}}$ ).

- 21. (Previously presented) The method as claimed in claim 13, wherein: based on results of the second evaluation, a plausibility check is carried out for results of the first evaluation method.
- 22. (Previously presented) The method as claimed in claim 15, wherein: the fill level measuring device works with ultrasound, for determining whether one of the predetermined fill levels (L<sub>MIN</sub>, L<sub>MAX</sub>) has been exceeded or fallen beneath, and emits transmission signals of a fixedly predetermined transmission frequency.

Claims 23 and 24 (Cancelled).